

5

DIGITAL BOOK

10 The present invention relates to a digital book, in particular for the reproduction of book, newspaper and magazine information and other documentation and publications in electronic or digital form by means of text, graphical, photo and/or video and audio information for operation through laymen.

15 The consumption of paper and with it the demand for raw materials are growing year for year. The ever growing population and the always increasing demand for information, but also the self-imposed competition-induced communication constraint cause an explosion-like expanding
20 flood of information which necessitates in always shorter intervals an immense consumption of paper, which thus is not only a burden to the environment but also entails an economic disadvantage as regards the transportation, stock-keeping and recycling costs as well the speed necessary to make available publications. Owing to modern
25 information technologies it has indeed become possible to produce a large part of the information via computers, to offer it for instance via internet, online services or data bases or to market it in the form of CDs, however such information can be consumed by the consumer
30 via PCs, laptops and notebooks only, which presupposes that at least one of the above-mentioned computers is purchased, that necessary applications are installed and that one has to be familiar with the use thereof before
35 a first publication can be read.

The afore-mentioned reasons and the investment costs associated therewith, the necessary time and the, from

09508794-050100

the view of a technical layman, special knowledge required for installing and operating hardware and software make it difficult for a large part of the population to take advantage of electronic publications. But also older or handicapped persons often do not find access to computers, since, without basic knowledge, operation and handling are not possible for a layman or possible with difficulties only, or the complexity of the user interfaces imposes excessive demands on these persons.

Moreover, laptops and notebooks, due to their various drives and multitude of input and output interfaces for specific applications, are of large volume and weight, and they are equipped with a keyboard for the entire particular font and with just one single screen or display. However, there are applications in which on the one hand the relatively costly and space-consuming keyboard is unnecessary and on the other hand the display or display/operating area provided by just one single screen is too small for specific applications.

Laptops and notebooks, due to their purpose as working tool and the constructionally necessitated or constructional features associated therewith, primarily are no ergonomic, i.e. handy and easy-operation means of information to take up, e.g. belletristic literature or for reading reports, articles, commentaries and news from magazines and newspapers or for studying publications in relaxed posture or in situations where no supporting surface is available. Expenditure and time of operation often stand in no relation to the often spontaneous demands which moreover are frequently to be settled shortly, e.g. looking up information from a lexicon, a telephone directory or a television magazine.

✓ The document US 5,534,888 A1 reveals an electronic book comprising two display parts adapted to be folded open in the manner of a book, as well as a central part joining together these two display parts.

5

A simple ergonomic and compact electronic device as actual substitute for books, magazines or newspapers for universal use in different situations in life, which is uncomplicated and comfortable to hold and operate for

10

technical laymen and at the same time has little optical irritations for undisturbed reading and manipulating a large variety of different publications, is not known so

✓

far. The electronic book known from US 5,534,888, for handling through the user, requires often inconvenient

15

and time-consuming complicated operations since a multitude of keys arranged in inconvenient manner in terms of ergonomics is to be operated, with the functionality thereof being predetermined and the space available for the display being thus curtailed. In case of an elec-

20

tronic book known from US 5,534,888 A1 the operation takes place with the aid of an auxiliary display on the outside of the book covers (display elements), with the result that the user must shut the electronic book in

25

order to carry out specific adjustments. Furthermore, the keys can be operated in single manner only. On the reverse of the central part there is arranged a multitude of electrical connectors which are hidden behind protective flaps and which, if necessary, must be identified by the user with technical knowledge and must be

30

made accessible by folding up the protective covers. In case electrical lines are connected to the electrical connectors, the electronic book of the prior art can no longer be held on the book back in the manner of a book or be placed on a support.

35

09508794.050100

It is thus the object of the invention to make available a digital book of the type indicated at the outset, which in contrast to the prior art offers, despite a compact construction, on the one hand a considerably enlarged display area and on the other hand handling options that are user-friendly, simple and easily understandable for computer laymen, to enable the same to read comprehensive literature, e.g. scientific works, encyclopedias or also belletristic literature, in order to offer the advantage to the user, also in comparison with a conventional more voluminous and heavier book, to at least read and/or possibly work on an arbitrary number of pages via e.g. just two digital book pages in handy form. The reading and viewing habits of traditional readers of books, magazines and newspapers need to be considered in this respect, who expects as irritation-free as possible viewing of the publications or document information indicated and are repelled by an impression too closely oriented along computer technology, e.g. as regards certain forms of operating elements or due to other overstrain, as it often occurs in case of older people or technical laymen who refuse to use an electronic or digital book. What is to be ensured in this respect is safe and ergonomic holding and operation in different situations, e.g. when walking, lying or if no other supporting surface is available, as well as simple and understandable handling with a minimum or lacking previous knowledge or for instance in case of a handicap. This is to provide uncomplicated and constant operability despite different possibilities of use and a multitude of tasks. It is intended to render possible fast and reduced operation with a minimum of changes in posture during reading.

The object underlying the invention is met by the subject matters of the independent patent claims.

09508794 "060100

Advantageous developments of the invention are defined by the features indicated in the dependent claims.

The digital book according to the present invention is advantageous since it represents a genuine alternative to a traditional book, presupposing first of all the viewing and reading habits of the user and requiring no specific technical (computer) knowledge. Furthermore, in comparison with the known prior art.

- a) the reading and/or working area is enlarged through operation by means of rear-side operating elements,
- b) pages can be read in the manner of traditional book pages, without disturbing elements, e.g. menu list, icons, operating elements etc.,
- c) this device can be used without specific preparations in any situation and in an arbitrary body position, e.g. in case of confinement to bed of the user.

Multifunction input means (Figs. 11/60h) located in the range of action of the holding hand, which can be combined (Figs. 13 to 19) and can be programmed or switched over under software control (Figs. 13 to 22) and preferably are formed as keys located on the side directed away from the display area and operated by means of the fingers of the holding hand (Figs. 3, 4, 5, 6, 11, 13 to 19), with functions being displayed only if required and being handled marginally without disturbing the document (Figs. 15a, 16 to 21):

- a) faster completion of operating routines

b) minimization of movement and avoiding constant changes in position of the hand holding the display means

5 c) reduction of the technical impression and/or expenditure with utmost utility with the least possible amount of input elements

10 d) better distribution of the tasks to the individual fingers

e) enlargement of the front display area

15 e) flexibility through the additional possibility of combination with other input means, such as e.g. the display area and/or actual operating elements which can also be operated with the other hand and/or voice input

20 f) easier orientation e.g. for visually impaired and blind persons (presupposed is of course the reading out of the book via an audio output)

25 User interface (Fig. 9) located on the underside of the digital book, preferably in the folding hinge of a two-part display unit (Figs. 1 to 6, 11), which is the holding grip of a one-part display unit (Fig. 12h), for coupling by means of cable connectors preferably with jack plugs, in order to effectively connect different devices, apparatus and means to the book (Figs. 1, 2, 3, 5, 30 11, 25, 26) and/or to serve as a support for the book station (Fig. 5) and to supply data information and/or energy to the digital book by means of signal transmission (Fig. 1):

35

a) uncomplicated connection

09508794-060100

- b) avoiding damage in case of improper handling
 - c) reduction of interfaces and associated therewith reduced production costs
 - d) book back free from cables and plugs for better placement e.g. on a table surface or in the lap
 - e) use both for cable connection and for the holding pin of the supply station
 - f) more favorable symmetry and balance in case of possibly arising strain loads through connected supply cables
 - g) lesser irritation through disturbing cables
 - h) reduction of the "technical impression" on the side of the user
- Ergonomically shaped display back side and flexibility
- a) handier, more pleasant and safer holding during operation and transport
 - b) more compact construction with sensible and optically advantageous accommodation of the necessary electronics
 - c) predetermined bending location for easier bending (flexibility)
 - d) protection of operating elements disposed on the rear side/laterally

09508794-090100

- 5

10

30

35

text side, without the current book page being covered or blanked out thereby. Besides, cross-references, reference hints etc. can be indicated by marking, e.g. by tapping the source mark with the screen pen, without requiring "page turning".

Due to the possibility of separating the screens of the digital book, it is possible, starting from a basic configuration thereof (which is intended for reading only), to match the secondary screen to the needs of the user in accordance with the requirement profile and the prior art, and the range of capabilities of the digital book can thus be expanded. For example, the secondary screen can be designed to be pressure-sensitive whereby a screen page can be written on in hand-writing by means of the screen pen while the written text quasi simultaneously can be indicated on the main screen in printed letters, and optionally in another language by means of a translation function of the loaded software. This renders possible e.g. more rapid and convenient preparation and revision of business letters.

A digital book having a first optimized user interface according to the invention, for simplified operation with minimum technical information, comprising at least one input unit located on a right and/or left side of the digital book for manipulating the information displayed and/or for effecting a change in operating state and/or setting and/or for loading document information and/or for switching to another operating mode, however without restriction thereto, with the main input element(s) or key element(s) being advantageously disposed in the gripping edge on the side (60h) of the digital book facing away from the display side, such that operations possibly may be carried out at a location where

09508794-060100

the display unit (10) is held, by means of the fingers of the holding hand.

Fig. 11 shows in exemplary manner an upper left position, preferably there is provided a position laterally in the middle of a display side, since the central position constitutes a more neutral starting position for operation, as will be pointed out in the subsequent description of the figures, in which however preferably three combinations keys, shown preferably in the exemplary figures, can be replaced by other operating elements, provided that these at least in part fulfil tasks by way of their properties, which include for example the selection and activation of information displayed on the display area and/or moving pages and/or at least the option of displaying a first item of information on the display area and/or to release an already displayed first item of information, e.g. by deactivation of an activation blocking means (ES) to be operated via an arbitrary input provided therefor, e.g. via touchscreen preferably also in the region of lateral gripping edge of the display (20). It is left open whether there is only service of real operating elements and/or in combination with a sensitive display area and/or in combination with speech, since this is dependent first of all (as shown in Figs. 16 to 19) on how the properties of the display medium are designed, e.g. as touchscreen or as a mere display screen. It is basically also possible to arrange other operating elements at other locations of the display unit without affecting the scope of protection.

The operating elements are provided in different designs and arrangements. The operating area may also be equipped e.g. with a slide pad and/or trackball and/or a

007090" 46280560

A digital book with an additional optimized user interface according to the invention for simplified operation with minimum technical information, comprising at least one or plural display area(s) of sensitive design, via which, by touching an arbitrary, but predetermined location, first operating information of an invisible functional choice or operating information is made available, i.e. displayed, which can be handled further. This takes place preferably by identification of a functional choice or functional group to be displayed via fixed position information (60'V) offered, for example, by a first corner of the display area and/or a central location on a lateral side of the display area. Preferably, it is provided for the normal reading mode to keep blanked out or invisible a multiplicity of irritating and disturbing functions or operating information to be indicated on the display area for operation and to make available corresponding functional or operating information only in case of necessity, with all functions being made visible or available either all at once or one functional group separately from at least one further functional group for manipulation thereof. The advantage hereof is an irritation-free or undisturbed document page displayed, similar to a book (illustrative examples are shown in Figs. 19, 20, 21).

An additional advantageous development, which however is not restricted thereby, effecting the installation of functional or operating information by an initialised document, provides the possibility of separating the display area into regions allowing the layman sensible operation with respect to specific functions of the publication indicated, e.g. if a coupled memory with docu-

ment information (50') makes available all functions and operating information, respectively, required for service of this document, in the display unit in invisible manner at that location where the coupled memory is located. The layman thus has the possibility of requesting only that operating information that is directly associated with the initialized document.

00508794 060100
A digital book comprising an additional optimized user interface according to the invention for simplified operation with minimum technical information, comprising at least a first solid-state coupling device (50) provided preferably in the upper part of the digital book and serving preferably for a memory card (50'), but being not restricted thereto, which by means of a coupling operation, preferably by insertion of the solid-state element, triggers one or several processes in the digital book, which facilitates handling of pages by a laymen insofar as e.g. the content of the coupled solid-state body, without further ado by the user, endeavors to carry out the task desired e.g. by introduction of the body (50') into the receiving opening designed for this purpose. For example, the contents of a memory card with book information is displayed after successful coupling, without additional activity by the user, or at least a first item of information is made available that only needs to be verified by the user (Fig. 24). The initialization request necessary therefor preferably is provided by the digital book, after identification of the coupled solid-state body. To this end, the already known plug and play technology may be used to ensure recognition of the solid-state body (cf. in this respect also Fig. 22 or Fig. 23).

An additional advantageous means for easy operation with minimum technical information according to the in-

vention, by coupling one or more solid-state bodies with the digital book according to the invention, consists in that these solid-state elements contain software and/or hardware components, such as e.g. electronic means (integrated circuits, battery, memory, transmitter and/or receiver for information transfer without cables, etc.) which in some way or other, as outlined, preferably without further ado of the user, expand the range of capabilities with regard to the information to be indicated, which is input into the digital book via the solid-state means, and/or takes over operating functions that cannot be carried out by the user, or in a restricted scope only, due to lack of an alphanumerical keyboard.

A further advantageous means for simple operation with a minimum of technical information, by coupling one or more solid-state bodies with the digital book according to the invention, is the automatic installation and/or setting of the digital book - effected by coupling of a solid-state memory with the digital book -, for example by programming the functional keys of the digital book for optimum handling of the document stored in the solid-state memory (Fig. 22) and the corresponding operating information and/or e.g. the automatic switching over from a separate-display operating mode to a combined-display operating mode, and vice versa, preferably automatically by coupling and/or decoupling a first and/or second solid-state memory with document information to be displayed (Fig. 23).

A digital book with an additional optimized user interface according to the invention for simplified operation with a minimum of technical information makes use of a coupling by means of cable connectors via preferably only one interface on the bottom side of the digital

book (70'), preferably in the pivot hinge of the book in case of two-part or multi-part display sections which in case of one-part display sections is the gripping handle, for receiving for example a jack plug (70'). This provides the advantage that the interface is sturdy, uncomplicated in operation and that the contact positions necessary for establishing contact can be accommodated along an arbitrary length of the jack plug, since introduction is not hindered by the constructionally necessitated depth of the digital book. The preferably only one interface is designed such that the electronic means of the digital book can be effectively connected to a large variety of different devices, means and apparatus by means of signals for transmitting data for example in bidirectional and serial fashion and/or energy. To this end, it is possible to couple different peripheral apparatus, such as e.g. printers and/or telephone and/or modem and/or PCs and/or laptops and/or charging devices, which are cited as examples only. For doing so, the layman user just needs to plug in the corresponding cable connector and latch the same, if there are provisions to this effect. Another function of this interface consists in receiving the guide and supply pin of the book station, which has the task of supplying energy and/or data information to the digital book, which for example in accordance with the particular design can be provided on the book station or in the digital book. This supply plug at the same time serves as a stabilization pin (Figs. 5/7) of the digital book to be arranged thereon in upright position, namely as two-part book in the closed state and/or as one-part book in the opened state via the interface integrated in the handle (not shown).

0050794 050100

Embodiments of the invention will be described in detail in the following with reference to a number of drawing figures:

5 Fig. 1 shows a schematic plan view of a display-part coupling embodiment of the digital book according to the invention with two display parts in the folded open condition of the book casing along with schematically indicated installations and additional elements for the digital book, including the separating and coupling possibilities of the essential parts thereof.

10 Fig. 2 shows a simplified schematic plan view of the display-part coupling embodiment of the digital book according to the invention with two display parts in the folded open state of the book casing along with additional elements, similar to the representation shown in Fig. 1.

15 Fig. 3 shows a schematic side view of a permanently connected embodiment and/or of the main part of the display-part coupling embodiment of the digital book with two display parts, along with preferably juxtaposed combination key elements in the region of the gripping edge for operation thereof.

20 Fig. 4 shows, partly in section, a bottom view of the permanently connected embodiment and/or the display-part coupling embodiment of the closed digital book according to the invention with two display parts, for use of the preferably juxtaposed combination key elements in the region of the gripping edge for operation e.g. by a left-handed and/or right-handed person if e.g. a display area adapted to be written on is disposed on the right side of the digital book.

00508794 060100

5

10

15

25

30

35

according to the invention in the form of a configuration of units and components for operation of the digital book, however without restriction to this block circuit diagram.

5

Fig. 11 shows a representation of the permanently connected and/or display-part coupling embodiment of the digital book according to the invention, however without restriction thereto, and of the optimized user interfaces underlying the invention for simple operation by a layman and for reducing technical information.

10

Fig. 12 shows a representation of different modes of appearance of the digital book according to the invention, however without restriction thereto, in the form of a one-part or multi-part, permanently connected or display-part coupling embodiment.

15

Fig. 13 shows the partial aspects underlying the digital book according to the invention, for optimizing, i.e. simplifying operation along with simultaneous reduction of irritating information and/or technical designs.

20

Fig. 14, by way of an example of a folded-open two-part digital book according to the invention, however without restriction thereto, shows the provision of operating information and the further handling thereof by means of operating elements located away from the display area and/or by means of an input via a sensitive input area, as well as the provision of first functional information as well as further operation via the sensitive input area.

25

30

Fig. 15 shows the functional possibilities of a minimum configuration of operating elements of the digital book according to the invention, comprising a first function

35

007090"46280560

5

10

20

25

30

Fig. 19, by way of the example of one-part and two-part display sections, shows the programming of the three operating elements for a digital book, which are arranged preferably on the rear side, as rapid-function operating elements for frequent routine operations, using as example a first function of simple-operation operating elements, for example for moving the pages within a book document and processing of not so often needed functions via the display area, with these functions being made available by touching a location on the display area and being programmed for example by initialization of a coupled book document.

Fig. 20, by way of the example of a corner function and a function in the middle of a lateral edge displayed in the display area, shows an embodiment of Fig. 19, with lateral edge operations in the region of the gripping edge of the display unit being realized in a document edge and/or frame, in order not to irritate or disturb a displayed document.

Fig. 21, by way of the example of two corner functions displayed in the display area, shows an embodiment of Fig. 19, in which the lateral edge operations in the region of the gripping edge are realized in a document edge and/or frame in addition, in order not to irritate or disturb a displayed document.

Fig. 22, by way of the example of a one-part embodiment of the present invention, shows the automatic and software-controlled programming of operating elements and the resulting change in the displayed operating information by a coupled memory medium or an initialized document.

Fig. 23, by way of the example of a two-part embodiment of the present invention, shows the automatic switching over of a combined-display operating mode, during coupling of a second book document with the digital book, to a separate-display operating mode with corresponding display of the document on the display area as well as automatic switching over from a separate-display operating mode to a combined-display operating mode associated with a reverse process.

Fig. 24, by way of the example of a two-part embodiment of the digital book according to the invention, shows the activation and/or deactivation process of the digital book associated with coupling of a solid-state memory, as well as the attempt of installing and/or displaying the contents of the solid-state memory, which is effected automatically by coupling said solid-state element.

Fig. 25, by way of the example of a two-part embodiment of the digital book according to the invention, shows the coupling possibility of different external apparatus or means via a multifunction interface arranged at the bottom side of the digital book and designed as interface for cable connectors and/or of the supply station.

Fig. 26 shows in exemplary manner a hardware coupling and decoupling possibility by attaching or removing different hardware parts via the pivot hinge of a two-part digital book, which upon removing a part is the gripping handle of a one-part digital book, in which electronics is accommodated.

Fig. 26a, by way of the example of a one-part starting basis, shows the coupling of an exemplary gripping handle, as described in Fig. 26, or of a book cover of an

arbitrary material shown to be flexible in the example,
or the coupling of a laptop keyboard.

5 Fig. 27 shows the ergonomic design of the present inven-
tion along with the thus created compact construction
and the improved holding and operating possibilities,
both of a one-part and of a multi-part digital book.

10 Fig. 28 shows a flexible digital book according to the
invention by way of the example of a display part, and
the flexible design at least of the body or casing com-
prising the display area, as an example of a pressure-
sensitive design possibility e.g. by using an electron-
ics-enclosing casing of foamed material.

15 Fig. 29 shows a flexible digital book according to the
invention, by way of the example of a display part, and
the flexible design of display area and casing, as an
example of an at least partly flexible design possibili-
20 ty by tightening e.g. a polymer display in a casing
frame on two sides.

25 Fig. 30 shows several flexible digital books according
to the invention by way of the example of one or two
display parts with operating possibility, in which for
example one or several polymer displays are adhered in
at least partly transparent plastics or plastics-similar
material for strengthening.

30 Fig. 1 shows a schematic plan view of a display-part
coupling embodiment of the digital book according to the
invention, comprising two display parts 1, 2, in the
folded open condition of the book casing along with
schematically indicated installations and additional
35 elements EP, EP2, HP, NP2, 14, 5, 5', B for the digital
book adapted to be coupled, including the separation and

00503794, 050100

Fig. 2: The display-part coupling embodiment of the digital book according to the invention contains a display unit 1, 2, 3, 4 which is at least of two-part construction and is arranged such that the main part 1 with at least one screen 3 and the secondary part 2 with at least one screen 4, in the folded-open state of the casing, present themselves to the user, like pages of a book, for looking at and optionally, for working on as required (cp. also Fig. 2).

Fig. 3: The display part of the main part of the display-part coupling embodiment of the digital book according to the invention, in the closed condition of the casing, is adapted to be plugged into a supply unit VE (cf. Fig. 5) via a guide and supply pin 7 having a

pair of power supply contacts 8 and a multiplicity of contact rings 9 for supplying and outputting information, said supply unit VE having a supply unit opening VE' for inputting and outputting information signals and/or for supplying energy and for accommodating the digital book (cp. Fig. 5). The book back part BR contains furthermore a light-emitting diode L for indicating the charging state of battery B. The juxtaposed combination key elements are arranged in the region of the gripping edge.

In a modified embodiment, main part and secondary part may also be fixedly or permanently connected to each other in pivotable manner, without the provision that both parts can be separated from each other.

Fig. 4 shows partly in section a bottom view of the main part of the permanently connected and/or of the display-part coupling embodiment of the closed digital book according to the invention for use e.g. by a left-hander and/or a right-hander if e.g. a display area adapted to be written on is disposed on the right side of the digital book, with the representation containing the elements described hereinbefore. The casing contains, in a guide and supply opening 7', countercontacts 8' for power supply and/or countercontacts 9' for inputting and outputting information. The book back part BR (cp. also Fig. 3) is provided with a preferably rechargeable battery B for power supply of the electronic units and components of the digital book and for driving the screens 3, 4.

Fig. 5 shows, as already indicated, a perspective view of the permanently connected and/or of the display-part coupling embodiment with two display parts of the digital book according to the invention in the closed state,

as well as a perspective view of a supply unit VE having a receiving opening VE'. The guide and supply pin projecting from the supply unit serves, among other things, for stabilization of the digital book in the supply unit. The digital book is shown in relation to the supply unit VE in a condition during removal of the digital book or in a condition during introduction of the same into the supply unit VE. Supply unit VE comprises a connecting cable 89 for inputting and/or outputting information, for example from and/or to a PC and/or a modem, and/or for supplying energy for powering the electronic units and components and for driving the screens of the digital book. Juxtaposed combination key elements are arranged in the region of the gripping edge.

Fig. 6a, Fig. 6b and Fig. 6c show different perspective views in the "folded open" condition a permanently connected and/or a display-part coupling embodiment of the digital book according to the invention with two display parts, for reading and/or e.g. writing on a display area adapted to be written on. Writing on the display area adapted to be written on and designed to be pressure-sensitive, in the example shown, takes place by means of a screen pen 15. Instead of using screen pen 15 for marking or triggering a specific function, it is of course also possible to press with a fingertip against a specific location of the screen, as it is known in connection with the so-called touchscreen.

Fig. 7a, Fig. 7b, Fig. 7c, Fig. 7d, Fig. 7e and Fig. 7f show, as already indicated, different representations of the permanently connected and/or of the display-part coupling embodiment with one, two and three display parts of the digital book according to the invention in different applications, these representations indicating various advantages of the digital book.

Fig. 8 shows the representation of a possible structure of a secondary part 2a, 2b in form a double screen 4a, 4b similar to a folding map or time organizer in the "folded open" condition of the digital book for an application with three screens 3, 4a, 4b. In the embodiment shown the casing of the digital book comprises two folding axes A1, A2.

Fig. 9a and Fig. 9b show representations of the same embodiment as shown in Fig. 8, in the folded together or "folded shut" condition of the digital book.

Fig. 10 shows, as already indicated, a block circuit diagram of the display-part coupling embodiment of the digital book according to the invention, showing the configuration of units and components for operating the digital book. In addition to the elements described hereinbefore, the block circuit diagram comprises a display unit D having two screens 3, 4, two screen drivers or graphic cards 3', 4', a control unit 10 with means for receiving, storing, processing and reproducing information, in which the information may be present in the form of text, image, graphical, audio and/or video information, an interface unit 11 for inputting and outputting information and for supply energy, said interface unit 11 including an information interface 12 and a power supply means 12 for supplying power to the units D, 10, 11 from the supply unit VE. Control unit 10 contains an EPROM, a ROM, a RAM, a CPU, a control means ST and a driver circuit TR, with these elements being interconnected via a bus line BL. The screen drivers or graphic cards 3', 4', the operating unit 6 with its operating elements, the control unit 10 and the information interface 12 are connected to each other via the afore-mentioned bus line 14.

Fig. 11 shows a representation of the permanently connected and/or of the display-part coupling embodiment with two display parts of the digital book according to the invention, and the optimized user interfaces for simple operation by a layman and for reducing technical information, with five individual

Fig. 11 shows a digital book according to the invention comprising an optimized user interface for simplified operation with a minimum of technical information, having at least one manipulation region 60h located on the right and/or left side of the digital book, in particular for manipulating the displayed information and/or for effecting a change in operating state and/or setting and/or for loading document information and/or for switching over to a different mode of operation, with the manipulation region 60h in this embodiment having functional keys F1, F2, F3 arranged on the rear side (i.e. the side directed away from the display area) as well as a pressure-sensitive input region 60t on the front side. Input region 60t optionally may also be realized by other technical means, e.g. capacitive proximity switches, miniature keys.

The manipulation region 60h is arranged such that manipulation operations should be possible at a location where the display unit 10 is held, by means of the fingers of the holding hand. Fig. 11 shows in exemplary manner an upper left position, and preferably there is provided a position in the middle of a lateral edge of a display side, since the middle position constitutes a more neutral starting position for operation, as will be pointed out in the subsequent description of the figures; there are provided preferably three combination keys.

001090"46780560

at least in part fulfil tasks by way of their properties, which include for example the selection and activation of information displayed on the display area and/or moving pages and/or at least the option of displaying a first item of information on the display area and/or to release an already displayed first item of information, e.g. by deactivation of an activation blocking means (ES) to be acutated via an arbitrary input provided therefor, e.g. via touchscreen preferably also in the range of the lateral gripping edge of the display (20). It is left open whether there is only service of real operating elements and/or in combination with a sensitive display area and/or in combination with speech, since this is dependent first of all (as shown in Figs. 16 to 19) on how the properties of the display medium are designed, e.g. as touchscreen or as a mere display screen. It is basically also possible to arrange other operating elements at other locations of the display unit without affecting the scope of protection. The operating elements are provided in different designs and arrangements. The operating area may also be equipped e.g. with a slide pad and/or trackball and/or a multi-function key etc. or the corresponding key areas can be designed as induction areas or switches.

A digital book with an additional optimized user interface according to the invention for simplified operation with minimum technical information, comprising at least one or plural display area(s) of sensitive design, via which, by touching an arbitrary, but predetermined location, first operating information of an invisible functional choice or operating information is made available, i.e. displayed, which can be handled further. This takes place preferably by identification of a functional choice or functional group to be displayed via fixed position information (60'V) offered, for example, by a

09508794-060100

first corner of the display area and/or a central location on a lateral side of the display area. Preferably, it is provided for the normal reading mode to keep blanked out or invisible a multiplicity of irritating and disturbing functions or operating information to be indicated on the display area for operation and to make available corresponding functional or operating information only in case of necessity, with all functions being made visible or available either all at once or one functional group separately from at least one further functional group for manipulation thereof. The advantage hereof is an irritation-free or undisturbed document page displayed, similar to a book (illustrative examples are shown in Figs. 19, 20, 21). An additional advantageous development, which however is not restricted thereby, effecting the installation of functional or operating information by an initialised document, provides the possibility of separating the display area into regions allowing the layman sensible operation with respect to specific functions of the publication indicated, e.g. if a coupled memory with document information (50') makes available all functions and operating information, respectively, required for service of this document, in the display unit in invisible manner at that location where the coupled memory is located. The layman thus has the possibility of requesting only that operating information that is directly associated with the initialized document.

A digital book comprising an additional optimized user interface according to the invention for simplified operation with minimum technical information, comprising at least a first solid-state coupling device (50) provided preferably in the upper part of the digital book and serving preferably for a memory card (50'), but being not restricted thereto, which by means of a coupling

09508794-060100

operation, preferably by insertion of the solid-state element, triggers one or several processes in the digital book, which facilitates handling of pages by a laymen insofar as e.g. the content of the coupled solid-state body, without further ado by the user, endeavors to carry out the task desired e.g. by introduction of the body (50') into the receiving opening designed for this purpose. For example, the contents of a memory card with book information is displayed after successful coupling, without additional activity by the user, or at least a first item of information is made available that only needs to be verified by the user (Fig. 24). The initialization request necessary therefor preferably is provided by the digital book, after identification of the coupled solid-state body. To this end, the already known plug and play technology may be used to ensure recognition of the solid-state body (cf. in this respect also Fig. 22 or Fig. 23).

An additional advantageous means for easy operation with minimum technical information according to the invention, by coupling one or more solid-state bodies with the digital book according to the invention, consists in that these solid-state elements contain software and/or hardware components, such as e.g. electronic means (integrated circuits, battery, memory, transmitter and/or receiver for information transfer without cables, etc.) which in some way or other, as outlined, preferably without further ado of the user, expand the range of capabilities with regard to the information to be indicated, which is input into the digital book via the solid-state means, and/or takes over operating functions that cannot be carried out by the user, or in a restricted scope only, due to lack of an alphanumeric keyboard.

007090"4680560

A further advantageous means for simple operation with a minimum of technical information, by coupling one or more solid-state bodies with the digital book according to the invention, is the automatic installation and/or setting of the digital book - effected by coupling of a solid-state memory with the digital book -, for example by programming the functional keys of the digital book for optimum handling of the document stored in the solid-state memory (Fig. 22) and the corresponding operating information and/or e.g. the automatic switching over from a separate-display operating mode to a combined-display operating mode, and vice versa, preferably automatically by coupling and/or decoupling a first and/or second solid-state memory with document information to be displayed (Fig. 23).

A digital book with an additional optimized user interface according to the invention for simplified operation with a minimum of technical information makes use of a coupling by means of cable connectors via preferably only one interface on the bottom side of the digital book (70'), preferably in the pivot hinge of the book in case of two-part or multi-part display sections which in case of one-part display sections is the gripping handle, for receiving for example a jack plug (70'). This provides the advantage that the interface is sturdy, uncomplicated in operation and that the contact positions necessary for establishing contact can be accommodated along an arbitrary length of the jack plug, since introduction is not hindered by the constructionally necessitated depth of the digital book. The preferably only one interface is designed such that the electronic means of the digital book can be effectively connected to a large variety of different devices, means and apparatus by means of signals for transmitting data for example in bidirectional and serial fashion and/or

energy. To this end, it is possible to couple different peripheral apparatus, such as e.g. printers and/or telephone and/or modem and/or PCs and/or laptops and/or charging devices, which are cited as examples only. For doing so, the layman user just needs to plug in the corresponding cable connector and latch the same, if there are provisions to this effect. Another function of this interface consists in receiving the guide and supply pin of the book station, which has the task of supplying energy and/or data information to the digital book, which for example in accordance with the particular design can be provided on the book station or in the digital book. This supply plug at the same time serves as a stabilization pin (Figs. 5/7) of the digital book to be arranged thereon in upright position, namely as two-part book in the closed state and/or as one-part book in the opened state via the interface integrated in the handle (not shown).

A first optimized user interface for simple operation by a layman and for reducing irritating technical information, is at least one input unit located on a right and/or left side of the digital book for manipulating the information displayed and/or for effecting a change in operating state and/or setting and/or for loading document information and/or for switching to another mode of operation, however without being restricted thereto, with the main input element(s) or key element(s) being advantageously disposed in the gripping edge on the side (60h) of the digital book facing away from the display side, such that it should be possible to carry out operations at a location where the display unit (10) is held, by means of the fingers of the holding hand. In this respect, there is shown in exemplary manner an upper left position, and preferably there is provided a position laterally in the middle of a display

007050"46280560

side since the middle position constitutes a more neutral starting position for operation, as will be pointed out in the subsequent description of the figures.

5 Just as little restrictive is the use of three combinations keys, shown as preferred number in the embodiment illustrated, however, these can be replaced by other operating elements, provided that these at least in part fulfil tasks by way of their properties, which include
10 for example the selection and activation of information displayed on the display area and/or moving pages and/or at least the option of displaying a first item of information on the display area and/or to release an already displayed first item of information, e.g. by deactivation
15 of an activation blocking means (ES) to be operated via an arbitrary input provided therefor, e.g. via touchscreen preferably also in the region of the lateral gripping edge of the display (20). The embodiment shown leaves open whether there is only service of real operating elements and/or in combination with a sensitive display area and/or in combination with speech, since this is dependent first of all on how the properties of the display medium are designed, e.g. as touchscreen or as a mere display screen. It is basically also possible
20 to arrange other operating elements at other locations of the display unit without affecting the scope of protection. The operating elements are provided in different designs and arrangements. For example, the operating area may also be equipped e.g. with a slide pad and/or a trackball and/or a multifunction key etc., or the corresponding key areas can be provided as induction areas or switches.

35 An additional optimized user interface for simple operation by a layman and for reducing irritating technical information, consists in one or plural display area(s)

09508794-060100

of sensitive design, via which, by touching an arbitrary, but predetermined location, first operating information of an invisible functional choice or operating information is made available, i.e. displayed, which can be handled further. This takes place preferably by identification of a functional choice or functional group to be displayed via fixed position information (60'V), which is offered, for example, by a first corner of the display area and/or a central location on a lateral side of the display area. Preferably, it is provided for the normal reading mode to keep blanked out or invisible a multiplicity of irritating and disturbing functions or operating information to be indicated on the display area for operation and to make available corresponding functional or operating information only in case of necessity, with all functions being made visible or available either all at once or one functional group separately from at least one further functional group for manipulation thereof. The advantage hereof is an irritation-free or undisturbed document page displayed, similar to a book (illustration examples are shown in Figs. 19, 20, 21). An additional advantageous development, which however is not restricted thereby, effecting the installation of functional or operating information by an initialised document, provides the possibility of separating the display area into regions allowing the layman sensible operation with respect to specific functions of the publication indicated, e.g. if a coupled memory with document information (50') makes available all functions and operating information, respectively, required for service of this document, in the display unit in invisible manner at that location where the coupled memory is located. The layman thus has the possibility of requesting only that operating information that is directly associated with the initialized document.

00508794-060100

An additional optimized user interface for simple operation by a layman and for reducing irritating technical information, consists in at least a first solid-state coupling device (50) provided in the upper part of the digital book and serving preferably for a memory card (50'), but being not restricted thereto, which by means of a coupling operation, preferably by insertion of the solid-state element, triggers one or several processes in the digital book, which facilitates handling of pages by a laymen insofar as e.g. the content of the coupled solid-state body, without further ado by the user, endeavors to carry out the task desired e.g. by introduction of the element (50') into the receiving opening designed for this purpose.

For example, the contents of a memory card with book information is displayed after successful coupling, without additional activity by the user, or at least a first item of information is made available that only needs to be verified by the user (Fig. 24). The initialization request necessary therefor preferably is provided by the digital book, after identification of the coupled solid-state body. To this end, the already known plug and play technology may be used to ensure recognition of the solid-state body (cf. in this respect also Fig. 22 or Fig. 23).

An additional advantageous means for easy operation by coupling one or more solid-state elements with the digital book according to the invention, however without restriction thereto, consists in that these solid-state elements contain software and/or hardware components, such as e.g. electronic means (integrated circuits, battery, memory, transmitter and/or receiver for information transfer without cables, etc.) which in some way or other, as outlined, preferably without further ado of

00508794-060100

the user, expand the range of capabilities with regard to the information to be indicated, which is input into the digital book via the solid-state means, and/or takes over operating functions that cannot be carried out by the user, or in a restricted scope only, due to lack of an alphanumerical keyboard. A further advantageous means for simple operation by coupling one or more solid-state bodies with the digital book according to the invention, however without restriction thereto, is the automatic installation and/or setting of the digital book - effected by coupling of a solid-state memory with the digital book -, for example by programming the functional keys of the digital book for optimum handling of the document stored in the solid-state memory (Fig. 22) and the corresponding operating information and/or e.g. the automatic switching over from a separate-display operating mode to a combined-display operating mode, and vice versa, preferably automatically by coupling and/or decoupling a first and/or second solid-state memory with document information to be displayed (Fig. 23).

An additional optimized user interface for easy operation by a layman and for reducing irritating technical information makes use of a coupling by means of cable connectors via preferably only one interface on the bottom side of the digital book (70'), preferably in the pivot hinge of the book in case of two-part or multi-part display sections which in case of one-part display sections is the gripping handle, for receiving for example a jack plug (70'). This provides the advantage that the interface is sturdy, uncomplicated in operation and that the contact positions necessary for establishing contact can be accommodated along an arbitrary length of the jack plug, since introduction is not hindered by the constructionally necessitated depth of the digital book. The preferably only one interface is designed such that

00508794 060100

the electronic means of the digital book can be effectively connected to a large variety of different devices, means and apparatus by means of signals for transmitting data for example in bidirectional and serial fashion and/or energy. To this end, it is possible to couple different peripheral apparatus, such as e.g. printers and/or telephone and/or modem and/or PCs and/or laptops and/or charging devices, which are cited as examples only. For doing so, the layman user just needs to plug in the corresponding cable connector and latch the same, if there are provisions to this effect. Another function of this interface consists in receiving the guide and supply pin of the book station, which has the task of supplying energy and/or data information to the digital book, which for example in accordance with the particular design can be provided on the book station or in the digital book. This supply plug at the same time serves as a stabilization pin (Figs. 5/7) of the digital book to be arranged thereon in upright position, namely as two-part book in the closed state and/or as one-part book in the opened state via the interface integrated in the handle (not shown).

Fig. 12 shows a representation of different forms of appearance of the digital book according to the invention, however without restriction thereto, as one-part or multi-part, permanently connected or display-part coupling embodiment.

Fig. 13 shows the partial aspects underlying the digital book according to the invention for optimizing i.e. simplifying operation along with a simultaneous reduction of irritating information and/or technical designs by bundling the tasks and the corresponding input facilities concentrated in a portion.

There are shown two partial regions 1 and 2 representing the decisive aspects of the invention, which are related to each other, but also play a significant role separately from each other. On the basis of an embodiment, an opened digital book on the left side of Fig. 13, which shows the manipulation of displayed information by means of a cursor, the region 1 of Fig. 13 illustrates all partial aspects which together and/or separately from each other play a decisive role in simplifying operation of the digital book. This includes the reduction of the operating expenditure and the operating information via the possibility of operating section or key programming 60TPR of an initialized document Doc, which preferably is carried out automatically upon coupling of the information-carrying solid-state memory 50.

A further aspect 1b is the reduction of the operating expenditure and operating information by combination of input possibilities, such as e.g. real operating elements 60 which are combined with virtual operating elements 60' and 60'V and/or with speech input SpE, with the real operating elements preferably being adapted to be mutually combined, whereby the number of required operating elements can be reduced as well. In the illustrated embodiment, there are employed three keys 60, by means of which a multiplicity of functions can be carried out in the manner indicated hereinbefore. Further optimization of the operating function consists in distributing the operating elements to the fingers of the holding hand 1b 1, 2, 3, 4, 5 holding the display means, such that preferably the index finger 1, the middle finger 2 and the ring finger 3 operate the function keys, which renders possible considerably faster operation, while the small finger serves for locking the display part and the thumb is freely movable in order to effect, possibly in combination with speech and/or the real op-

erating elements or alone, operation of the virtual operating elements, i.e. input elements 60' displayed on the display area. To this end, the real operating elements 60 are preferably disposed on the rear side of a display area.

Further optimization of the operating functions 1c is the compressed arrangement of the operating elements AB in a portion FBh, which during holding of the display can be operated by means of the fingers, with said portion being preferably the area in the region of the lateral gripping edge, where the display-holding hand is situated most frequently, i.e. under ergonomic aspects in the middle region of a display side, since this location is the most balanced one for holding the display unit and is the most neutral one for operation by a left-hander or right-hander.

On the basis of an additional illustrative embodiment, in which an opened digital book is shown on the right side of Fig. 13 without indicating operating elements, the portion 2 of Fig. 13 shows all partial aspects of what, either commonly and/or separately from each other, plays a decisive role in reducing the elements disturbing or irritating in reading a document.

This includes the reduction of the real operating elements 60 to a necessary minimum and/or hiding the operating elements 60h e.g. on the side of the display unit 2b directed away from the display side. Fig. 2b illustrates the hidden arrangement of virtual manipulation elements, i.e. function elements 60', i.e. elements to be operated via the display area, which are made visible in common or separately from each other only in case of necessity, such that no first functional information for identifying e.g. a menu, is available and just the posi-

tion of a first input possibility 60'EF in relation to the display area provides orientation as to what functions are to be made available. Preferably, the corners 60'EF or central sides in the middle (not shown) of the display area serve for orientation. Fig. 2b shows furthermore an activation protection section 60ES which avoids inadvertent activation of a displayed or not displayed function 60' in the region of the gripping edge. To this end, an input e.g. via speech SpE or a real operating element 60', 60 or a different location on the display area, for example a corner 60MSF, is made for cancelling the input protection so that a function can be carried out. A further possibility of reducing disturbing elements 2c concerns already available operating and functional information, respectively, which for avoiding irritation of a displayed document, is located in an edge or a frame laterally of the document 60FR displayed, similar to the edge of a book or the passepartout of a picture.

The operation concentrated to a specific region, preferably with rear-side or lateral combination keys which advantageously should not be more than three mutually separate operating elements, however without restriction thereto, provides better distribution of a multiplicity of tasks and the functions associated therewith in consideration of the calmest possible or most relaxed position during carrying or holding the display unit.

Fig. 14, by way of the example of a folded open, two-part digital book according to the invention, however without restriction thereto, shows the provision of operating information and the further handling thereof by means of operating elements facing away from the display area and/or by input via a sensitive input area, as well as the provision of a first item of functional informa-

09508794.060100

tion and the further processing thereof via the sensitive input area.

Fig. 15 shows functional possibilities of a minimum configuration of operating elements of the digital book according to the invention, comprising a first function to perform a first task, using as example the provision of select information on the display area and the automatic and software-controlled reprogramming of the operating elements following said first operation, for fulfilling a second task, e.g. the selection and/or activation of a selected function or deactivation of said provision.

Fig. 16 shows the general combination possibility of an input area of the digital book according to the invention, using as example three real operating elements and their programming with regard to a first function and additional first functions rendered possible by combined operation, as well as the automatic, software controlled reprogramming of the operating elements by a first operating step, in order to fulfil another task in a second operating step.

Fig. 17, by way of the example of one-part and two-part display sections of the digital book according to the invention, shows the programming of the three operating elements preferably arranged on the rear side, for a digital book in which operation is effected via real operating elements only.

Fig. 18, by way of the example of one-part and two-part display sections, with an additional possibility of input via the display area (touchscreen), shows the programming of the three operating elements preferably arranged on the rear side, for a digital book in which the

09508794-060100

real operating elements in a first function realize the provision of operating information on the display area, for possible subsequent further processing or operating via a sensitive display area.

5

Fig. 19, by way of the example of one-part and two-part display sections, shows the programming of the three operating elements for a digital book, which are preferably arranged on the rear side, as rapid-function operating elements for frequent routine operations, using as example a first function of operating elements of simple operation, for example for moving the pages within a book document, and processing of not so frequently required functions via the display area, which are made available by touching a location on the display area and which are programmed for example by initialisation of a coupled book document.

Fig. 20, by way of the example of a corner function and a function in the middle of a lateral edge, shows an embodiment of Fig. 19, in which the lateral edge operations in the region of the gripping edge of the display unit are realized in addition in a document edge and/or frame in order not to irritate or disturb a document on display.

Fig. 21, by way of the example of two corner functions indicated in the display area, shows an embodiment of Fig. 19, in which the lateral edge operations in the region of the gripping edge of the display unit are realized in addition in a document edge and/or frame in order not to irritate or disturb a displayed document.

Fig. 22, by way of the example of a one-part embodiment of the present invention, shows the automatic and software-controlled programming of operating elements and

09508794.060100

the resulting change in the displayed operating information by a coupled memory medium or an initialized document.

5 Fig. 23, by way of the example of a two-part embodiment of the present invention, shows the automatic switching over of a combined-display operating mode, during coupling of a second book document with the digital book, to a separate-display operating mode with corresponding
10 display of the document on the display area as well as automatic switching over from a separate-display operating mode to a combined-display operating mode associated with a reverse process.

15 Fig. 24, by way of the example of a two-part embodiment of the digital book according to the invention, shows the activation and/or deactivation process of the digital book associated with coupling of a solid-state memory, as well as the attempt of installing and/or displaying the contents of the solid-state memory, which is
20 effected automatically by coupling said solid-state element.

Fig. 25, by way of the example of a two-part embodiment of the digital book according to the invention, illustrates the coupling possibility of different external apparatus or means via a multifunction interface arranged at the bottom side of the digital book and designed as interface for cable connectors and/or of the
25 supply station.
30

Fig. 26 shows in exemplary manner a hardware coupling and decoupling possibility by attaching or removing different hardware parts via the pivot hinge of a two-part
35 digital book, which upon removing a part is the gripping

09508794 050100

handle of a one-part digital book, in which electronics is accommodated.

5 Fig. 26a, by way of the example of a one-part starting basis, shows the coupling of an exemplary gripping handle, as described in Fig. 26, or of a book cover of an arbitrary material shown to be flexible in the example, or the coupling of a laptop keyboard or a card station.

10 Fig. 27 shows the ergonomic design of the present invention along with the thus created compact construction and the improved holding and operating possibilities, both of a one-part and of a multi-part digital book.

15 Fig. 28 shows a flexible digital book according to the invention by way of the example of a display part, and the flexible design at least of the body or casing comprising the display area, as an example of a pressure-sensitive design possibility e.g. by using an electronics-enclosing casing of foamed material.

20

Fig. 29 shows a flexible digital book according to the invention, by way of the example of display part, and the flexible design of display area and casing, as an example of an at least partly flexible design possibility by tightening e.g. a polymer display in a casing frame on two sides.

25

Fig. 30 shows several flexible digital books according to the invention by way of the example of one-part or two-part display units with operating possibility, in which for example one or several polymer displays are adhered in at least partly transparent plastics or plastics-similar material for strengthening.

30

35

09508794-060100

As already described hereinbefore, the secondary part 2 or secondary parts 2a, 2b is/are designed to be electrically and/or mechanically separable from the main part 1, so that the main part 1 can be used alone. The at least one operating unit 6 contains as operating elements directional keys and function keys which can be operated individually or in combination for various functions.

Display unit D may advantageously have a function to indicate a power supply status, preferably on the screen of main part 1.

The screen 3 or screens 3, 4 of display unit D preferably is/are flexible, which holds also for the casing, so that the digital book can be carried along like a notebook, for example in the inside pocket of a jacket. The screen 3 or screens 3, 4 advantageously may be provided with an adjustable background illumination system. The display on the screen 3 or screens 3, 4 as well as the background illumination may be designed to be turned on or off automatically when the casing is folded open or shut.

The casing may be provided with a holding means (not shown) for receiving the screen pen 15 for use as operating, writing, drawing and/or processing tool.

Hint concerning the exemplary character of what has been described

The present invention is not restricted to the embodiments described. Rather, the expert may carry out various modifications of the embodiments without having to leave the scope of protection as it is defined by the claims.